E/ECE/324
E/ECE/TRANS/505 } Rev 1/Add 29/Rev 1/Amend 1
21 April 1994

AGREEMENT

CONCERNING THE ADOPTION OF UNIFORM CONDITIONS OF APPROVAL AND RECIPROCAL RECOGNITION OF APPROVAL FOR MOTOR VEHICLE EQUIPMENT AND PARTS

done at Geneva on 20 March 1958

Addendum 29: Regulation No. 30

Revision 1 — Amendment 1

Supplement 4 to the 02 series of amendments — Date of entry into force: 1 March 1994

UNIFORM PROVISIONS CONCERNING THE APPROVAL OF PNEUMATIC TYRES FOR MOTOR VEHICLES AND THEIR TRAILERS

UNITED NATIONS

GE.94-21351

Paragraph 1, amend "240 km/h" to read "270 km/h".

Paragraph 2.17.1.3., amend to read:

"2.17.1.3. a conventional number denoting the nominal rim diameter and corresponding to its diameter expressed either by codes (numbers below 100) or in millimetres (numbers above 100);"

Paragraph 2.29., amend to read:

"2.29. "Speed category" means the maximum speed which the tyre can sustain, expressed by speed category symbol (see table below)."

Paragraphs 2.29.1. and 2.29.2. should be deleted.

Paragraph 2.29.3., renumber as paragraph 2.29.1. and add a new line to the table to read:

"

Speed category symbol	Maximum speed (km/h)
.	.
.	.
.	.
W	270

"

Add a new paragraph 2.31.3., to read:

"2.31.3. For speeds higher than 240 km/h (tyres classified with speed category symbol 'W') the maximum load rating shall not exceed the percentage of the value associated with the load capacity index of the tyre, indicated in the table below, with reference to the speed capability of the car to which the tyre is fitted.

Maximum speed (km/h)	Load (%)
240	100
250	95
260	90
270	85

For intermediate maximum speeds linear interpolations of the maximum load rating are allowed."

Paragraph 3.1.4., amend to read:

"3.1.4. An indication of the tyre's speed category, by means of the symbol shown in the table of paragraph 2.29. above;

Paragraph 5.4.1., footnote 2/, amend to read:

"2/ ... 8 for the Czech Republic, ... 23 for Greece, 24, 25 (vacant), 26 for Slovenia and 27 for Slovakia. Subsequent numbers ..."

Paragraph 6.3.3., amend the tolerance "$^{+0.40}_{-0.25}$ mm" to read "$^{+0.60}_{-0.0}$ mm".

Insert new paragraphs 11.3. to 11.3.2., to read:

"11.3. Tread-wear indicators:

11.3.1. As from the date of entry into force of this Supplement 4 to the 02 series of amendments, Contracting Parties applying this Regulation may no longer issue approvals pursuant to Supplement 3 to the 02 series of amendments with respect to the requirements of paragraph 6.3.3.

11.3.2. All new tyres manufactured from 1 October 1995 shall conform to the requirements of paragraphs 6.3.3. as amended by Supplement 4 to the 02 series of amendments."

Notes (placed after paragraph 12.3.),

Note 2/, amend the words "in inches" to read "by codes".

Note 3/, amend to read:

"3/ 1 for ... 15 (vacant), ... 22 for the Russian Federation. Subsequent numbers ..."

Annex 7, paragraph 1.2., add a new line to the table to read:

under column 'speed category': "W"
under column 'Radial tyres standard': "3.2 bar"

Annex 7, insert a new paragraph 2.2.3., to read:

"2.2.3. the maximum load rating associated with a maximum speed of 270 km/h for tyres with speed symbol 'W' (see paragraph 2.31.3. of this Regulation)."